



# WATER SPECIALIST 1" CI CONTROL VALVE



shown with optional bypass

- Solid state microprocessor with easy access front panel settings
- Three modes of operation; meter immediate, meter delayed, or time clock delayed
- Program in ppm, French degrees, German degrees, or cubic meters
- Fully programmable regeneration cycle sequence (maximum 9)
- Programmable regeneration cycle times
- Days override feature; 1 – 28 days available
- Backwash and brining ability to 22" diameter tanks
- Downflow/upflow regeneration
- Stores system configuration and operation data in nonvolatile memory
- Coin Cell Lithium battery back-up with a 24 hour carry over
- 12-volt output AC Adapter provides safe and easy installation
- Control valve design provides optimum service and backwash rates
- Treated water regenerant refill
- Mixing valve option available
- Low salt alarm
- 24-hour clock
- Reliable and proven DC drive

# Water Specialist 1" CI Control Specifications

Inlet/Outlet Fittings.....	3/4" to 1.5" NPS
Cycles .....	up to 9
Valve Material .....	Noryl (1) or equivalent
Regeneration .....	downflow/upflow

## FLOW RATES

Service @ 15 psi/1 bar drop (includes bypass and meter).....	102 lpm
Backwash @ 25 psi/1.7 bar drop (includes bypass).....	102 lpm

## OPERATING PRESSURES

Minimum/Maximum .....	20 - 125 psi (1.4 - 8.6 bar)
-----------------------	------------------------------

## OPERATING TEMPERATURES

Minimum/Maximum .....	40° - 110° F (4° - 43° C)
-----------------------	---------------------------

## METER

Accuracy .....	± 5%
Flow Rate Range.....	1 - 102 lpm
Volume Range .....	0.10 m <sup>3</sup> - 2000.0 m <sup>3</sup>
Totalizer .....	1 m <sup>3</sup> - 99,999 m <sup>3</sup>

## DIMENSIONS & WEIGHT

Distributor Pilot.....	1.050" OD Pipe (3/4" NPS)
Drain Line .....	3/4" or 1" NPT
Brine Line .....	3/8" or 1/2" OD Poly Tube
Mounting Base.....	2 1/2"- 8 NPSM
Height From Top Of Tank.....	7 3/8" (187 mm)
Weight .....	4.5 lbs (2 kg)

## ELECTRICAL SPECIFICATIONS

	<b>AC Adapter</b>
	<u>U.S.</u> <u>International</u>
Supply Voltage .....	120V AC .....
Supply Frequency .....	60 Hz..... 50 Hz
Output Voltage .....	12V AC..... 12V AC
Output Current .....	500 mA..... 500 mA

## TANK APPLICATIONS

Water Softener .....	6" - 22" Diameter
Water Filter (2) .....	6" - 22" Diameter

## CYCLES OF OPERATION

Choose up to nine regeneration cycles, in any order, with a wide range of available values:

Cycle .....	Range of values
Backwash.....	1 - 120 minutes
Rinse.....	1 - 120 minutes
Pause (service).....	1 - 480 minutes
Brine (co-current).....	1 - 180 minutes
Brine (counter-current).....	1 - 180 minutes
Refill (softener) .....	0.05 - 95.00 Kg
Refill (filter) .....	0.05 - 95.00 Liters

*Options: Backwash Filter, Bypass, Weather Cover*

Compatible with the following typical concentrations of regenerants or chemicals: Sodium chloride, potassium chloride, potassium permanganate, sodium bisulfite, chlorine and chloramines

1. Noryl is a trademark of General Electric

2. Filter tank size calculated @ 10 gpm of backwash per square foot of bed area/407 lpm per square meter of bed area